

R&S®CMW-ZASB

Automation Switch Box

Specifications



ROHDE & SCHWARZ

General data

| | | |
|---------------------------------|------------------------------|---|
| Connectors | | |
| USB ports | | two USB type-A connectors (emulates the unplugging of a USB device) |
| Trigger ports | | two BNC connectors (LVTTTL 3.3 V, max. 10 mA) |
| General purpose ports | | two mini DIN connectors, relay contacts (12 V/1 A max.) |
| Environmental conditions | | |
| Temperature | operating temperature range | 0 °C to +40 °C |
| | storage temperature range | –20 °C to +60 °C |
| Damp heat | | +25 °C/+40 °C, 95 % rel. humidity, cyclic, in line with EN 60068-2-30 |
| Mechanical resistance | | |
| Vibration | non-operating mode | |
| | sinusoidal | 5 Hz to 150 Hz, in line with EN 60068-2-6 |
| | random | 10 Hz to 300 Hz, in line with EN 60068-2-64 |
| Shock | | in line with MIL-STD-810E, method 516.4, procedure I, 40 g shock spectrum |
| Power supply | | |
| Rated voltage | | 100 V to 240 V AC (± 10 %) |
| Rated frequency | | 50 Hz to 60 Hz (± 5 %) |
| Rated current | | max. 1.0 A |
| Conformity | | |
| Electromagnetic compatibility | EU EMC Directive 2004/108/EC | in line with <ul style="list-style-type: none"> • EN 61326-1 • EN 61326-2-1 • EN 55011 (class B) • EN 61000-3-2 • EN 61000-3-3 |
| Electrical safety | | EU Low Voltage Directive 2006/95/EC not applicable |
| Dimensions | | |
| Dimensions | W × H × D | 127.7 mm × 82.5 mm × 24.6 mm (5.03 in × 3.25 in × 0.97 in) |

Ordering information

| Designation | Type | Order No. |
|---|---------------|--------------|
| Automation Switch Box | R&S®CMW-ZASB | 1202.9803.02 |
| External power supply 12 V, 30 W | | 3588.6403.00 |
| USB cable, 1.3 m, USB type A/USB type B | | 0041.9177.00 |
| Mini DIN plug (4-pin) | | 3024.4311.00 |
| R&S®CMW-ZASB Driver and Utilities, DVD | | 1202.9861.00 |
| Automation Manager | R&S®CMW-KT014 | 1203.3250.01 |

Service you can rely on

- Worldwide
- Local and personalized
- Customized and flexible
- Uncompromising quality
- Long-term dependability

About Rohde & Schwarz

Rohde & Schwarz is an independent group of companies specializing in electronics. It is a leading supplier of solutions in the fields of test and measurement, broadcasting, radiomonitoring and radiolocation, as well as secure communications. Established more than 75 years ago, Rohde & Schwarz has a global presence and a dedicated service network in over 70 countries. Company headquarters are in Munich, Germany.

Environmental commitment

- Energy-efficient products
- Continuous improvement in environmental sustainability
- ISO 14001-certified environmental management system

Certified Quality System
ISO 9001

Rohde & Schwarz GmbH & Co. KG

www.rohde-schwarz.com

Regional contact

- Europe, Africa, Middle East | +49 89 4129 12345
customersupport@rohde-schwarz.com
- North America | 1 888 TEST RSA (1 888 837 87 72)
customer.support@rsa.rohde-schwarz.com
- Latin America | +1 410 910 79 88
customersupport.la@rohde-schwarz.com
- Asia/Pacific | +65 65 13 04 88
customersupport.asia@rohde-schwarz.com
- China | +86 800 810 8228/+86 400 650 5896
customersupport.china@rohde-schwarz.com

R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG
Trade names are trademarks of the owners | Printed in Germany (ch)
PD 3606.6411.22 | Version 01.00 | June 2012 | R&S®CMW-ZASB
Subject to change

© 2012 Rohde & Schwarz GmbH & Co. KG | 81671 München, Germany



3606641122